

Physician Signature: \_\_

# **ABBOTT MRI-READY SYSTEM**

MRI Scan Clinician Checklist

This document is intended to be used as a guide for health care facilities.

Patient Name:			Date of Birth:		-	
Device Information						
Pacemaker		Product Model #:				
ICD	Manufacturer:	Product Model #:				
Lead Information:	:					
	Manufacturer:					
RV: $\square$ Yes $\square$ No	Manufacturer:	Product Model #:	Lead Length:	Lead Length: Implant Location:		
LV: □ Yes □ No	Manufacturer:	Product Model #:	Lead Length:	Implant Locati	on:	
	AN MRI SCAN <sup>a</sup> CARDIO e Abbott MRI-Ready Systems M					
MRI SYSTEM C					YES	МО
		MD C 12 1 1	11 1()			
	mplete MRI-Ready System with					
*Scanning patients who Scanning patients who implanted device are m	sence of lead extenders, lead ada o have other MR Conditional devices that are not in have other MR Conditional devices implanted in cr let. lude, but are not limited to, implanted leads with an	planted in cardiac tissue is acceptable provided a rdiac tissue that are at least 2 cm from the lead ele	l MR Conditional requirements for each imp	lanted device are met. tional requirements for each		
Lead impedance	e measurements are within the p	rogrammed lead impedance lin	nits.			
Pulse generator	is implanted in the left or right	pectoral region.				
	ıre™ CRT-Ps with Tendril™ STS	-	LY: Lead(s) implanted in righ	t atrium		
Pulse generator	has sufficient battery (not at end	l-of-life EOL).				
PRE-MRI SCAN	DEVICE SETTINGS				YES	ИО
Confirm pacing	capture thresholds are stable.					
Confirm capture threshold $\leq$ 2.5 V at a pulse width of 0.5 ms for RA and RV lead(s).						
Confirm capture threshold of $\leq$ 2.0V at a pulse width of 0.5 ms for the LV lead.						
□ VOO (Bipo	lar) 🔲 Pacing Off	☐ Intrinsic rate	e +bpm			
_	lar) □ Pacing Off t is required to program the devi					
REMINDER: It		ce to MRI Settings as part of th	e MRI scan workflow.	d using the Merlin™		
REMINDER: It  For pacemaker  Patient Care Sys  Print an MRI st  For Gallant",	t is required to program the devi	ce to MRI Settings as part of the tor™ handheld device is used, by the tor™ handheld device is used.	e MRI scan workflow.  verify that it has been enable or ogrammed parameters.			
For pacemaker Patient Care Sys Print an MRI su For Gallant*, adequate time	t is required to program the devi SONLY: if the SJM MRI Activa Stem (PCS) programmer. Summary report of the patient's Manual	ce to MRI Settings as part of the tor™ handheld device is used, by the tor™ handheld device is used.	e MRI scan workflow.  verify that it has been enable or ogrammed parameters.			
For pacemaker Patient Care Sys  Print an MRI su For Gallant", adequate time POST-MRI SCA	t is required to program the deview of the SJM MRI Activa them (PCS) programmer. Immary report of the patient's Machine of the patient's Machine of the MRI scan before the MRI scan before	ce to MRI Settings as part of th tor <sup>™</sup> handheld device is used, <sup>b</sup> v IRI Settings and permanently p ICDs & CRT-Ds ONLY: If MR e MRI Timeout expires.	e MRI scan workflow. verify that it has been enable programmed parameters. I Timeout is programmed, e			
For pacemaker Patient Care Sys  Print an MRI st For Gallant", adequate time  POST-MRI SCA  Disable the puls	t is required to program the devi s ONLY: if the SJM MRI Activa stem (PCS) programmer. summary report of the patient's N Entrant", and Neutrino" NxT to complete the MRI scan befor N DEVICE SETTINGS	ce to MRI Settings as part of th tor™ handheld device is used, <sup>b</sup> v IRI Settings and permanently p ICDs & CRT-Ds ONLY: If MR e MRI Timeout expires. Fing the permanently programn	e MRI scan workflow. verify that it has been enable programmed parameters. I Timeout is programmed, e		YES	NO
REMINDER: It For pacemaker Patient Care Sys Print an MRI su For Gallant*, adequate time POST-MRI SCA Disable the puls Confirm the per	t is required to program the deview of the SJM MRI Activa stem (PCS) programmer.  Immary report of the patient's Note to complete the MRI scan before Note 1 DEVICE SETTINGS  The generator MRI Settings, restormanently programmed settings are capture thresholds after the set of the set	ce to MRI Settings as part of th tor™ handheld device is used, <sup>b</sup> v MRI Settings and permanently p ICDs & CRT-Ds ONLY: If MR e MRI Timeout expires. ring the permanently programn are appropriate.	e MRI scan workflow.  verify that it has been enabled brogrammed parameters.  I Timeout is programmed, enabled been enabled brogrammed.	nsure that there is	YES	NO

### STEPS FOR AN MRI SCAN RADIOLOGY DEPARTMENT

Please refer to the Abbott MRI-Ready Systems Manual at manuals.eifu.abbott

MRI SCAN CONDITIONS	YES	NO
Confirm patient has a complete MRI-Ready System with MR Conditional pulse generator and leads(s).		
Confirm that no adverse conditions to MRI scanning are present.		
Select the correct Scan Parameters for your MRI equipment.		
Confirm the MRI Settings status (MRI Settings must be enabled before the scan).		
For Gallant <sup>™</sup> , Entrant <sup>™</sup> , and Neutrino <sup>™</sup> NxT ICDs & CRT-Ds ONLY: If MRI Timeout is programmed, ensure that there is adequate time to complete the MRI scan before MRI Timeout expires.  Patient must exit MRI scanner before (time and date)		
Perform the scan and monitor the patient.		
After patient receives MRI scan, disable the pulse generator MRI Settings.  Note: If you are not using the SJM MRI Activator handheld device, the MRI Settings must be disabled by the patient's device management physician, clinician or Abbott representative using the Merlin PCS programmer.		
IF SJM MRI ACTIVATOR DEVICE IS USED <sup>b</sup> (ONLY WITH PACEMAKERS)	YES	МО
Check MRI Settings status using the SJM MRI Activator handheld device.		
If MRI Settings are not enabled, enable MRI Settings before the MRI scan using the SJM MRI Activator handheld device.		
After patient receives MRI scan, disable MRI Settings using the SJM MRI Activator handheld device.		

## **Technical Support**

Abbott maintains 24-hour phone lines for technical questions and support:

1-818-362-6822

1-800-722-3774 (toll-free within North America)

- +46 8 474 4147 (Sweden)
- + 61 2 9936 1200 (Australia)

manuals.eifu.abbott

For additional assistance, call your local Abbott representative.

Physician Name:	Date:	
Physician Signature		

- a. For any additional information, including warnings, precautions, and potential adverse events, please refer to the Abbott MRI-Ready Systems Manual at manuals.eifu.abbott or visit cardiovascular.abbott/mriready.
- b. Do not bring any external devices, such as the Merlin PCS Programmers, SJM MRI Activator device or a smart phone or tablet running a mobile application, into the scanner magnet room (Zone IV).

This document is intended to be used as a guide for health care facilities.

Brief Summary: Prior to using these devices, please review the Instructions for Use for a complete listing of indications, contraindications, warnings, precautions, potential adverse events and directions for use.

" Indicates a trademark of the Abbott group of companies.

† Indicates a third-party trademark, which is property of its respective owner.

**Abbott** 15900 Valley View Court Sylmar, CA 91342 Tel: +1 818 362 6822

Cardiovascular.Abbott

© 2025 Abbott. All Rights Reserved. MAT-2205945 v3.0 | Item approved for U.S. use.

